



OPERATION AND MAINTENANCE

INSTRUCTIONS FOR

6538 SERIES

TWO TON PACKAGED HEAT PUMP

TABLE OF CONTENTS

I.	Specifications	2
II.	General Information	3
III.	Maintenance	3
IV.	Warranty	4

**I.
S**

SPECIFICATION

6538B871

MODEL NUMBER FOR OUTDOOR USE	SERIAL NUMBER ↑ TOP ↑
---------------------------------	--------------------------

ELEC. RATINGS: 115 VAC 60 HZ 1 PHASE

CIRCUIT #1 8.7 RLA 54.0 LRA 10.3 BCSC	COMPRESSOR 1450-214 MOTOR THERMALLY PROTECTED	CIRCUIT #2 RLA 8.7 LRA 54.0 BCSC 10.3
--	--	--

3.4 FLA	I.D. BLOWER MOTOR DATA H.P. 1/3	FLA N/A
2.8 FLA	O.D. BLOWER MOTOR DATA H.P. 1/3	FLA 3.7

19.0 AMP	MIN. CIRCUIT AMPACITY	AMP 16.6
20 AMP	MAXIMUM OVERCURRENT PROTECTIVE DEVICE	AMP 20
28.25 OZS.	R-22 CHARGE WEIGHT	OZS. 28.25

MINIMUM EXTERNAL STATIC PRESSURE .43 IN. W.C.

#12 0'-25'	MINIMUM SUPPLY CONDUCTOR GAUGE (COPPER)	0'-25' #12
#10 25'-40'	UTILISER DES FILS D'ALIMENTATION	25'-40' #10
#8 40'-63'	EN CUIVRE	40'-63' #8

WARNING: RISK OF ELECTRIC SHOCK. CAN CAUSE INJURY OR DEATH. DISCONNECT ALL REMOTE ELECTRIC POWER BEFORE SERVICING.

AVERTISSEMENT: RISQUE DE CHOC5 ELECTRIQUES. PEUT CAUSER DES BLESSURES ET MEME ENTRAINER LA MORT. COUPER LES SOURCES D'ALIMENTATION A DISTANCE AVANT LE DEPANNAGE.

RV PRODUCTS
DIV. OF AIRXCEL INC.,
WICHITA, KANSAS

LISTED ROOM AIR CONDITIONER 5K09	6538B180
--	----------

DESIGN PRESSURES
HI SIDE 300 PSIG / LO SIDE 150 PSIG

II. GENERAL INFORMATION

This packaged heat pump mounts below the floor of the vehicle. The innovative design makes it possible to maintain a smooth, free-flowing roof line for the vehicle. It also relocates all heat pump noise and condensate drainage off the roof to below the floor of the vehicle.

This heat pump contains a dual compressor system with each compressor connected to a separate refrigeration circuit. It combines the capacity of two roof mounted units into one highly efficient and compact package.

A. Air Conditioner

This heat pump operates a two-stage system in cooling running a single compressor when the air conditioning requirement is low, or with two compressors when maximum cooling is required.

The first compressor and refrigeration circuit is referred to as "1st Stage". The second compressor and refrigeration circuit is referred to as "2nd Stage". First and second stage will operate as indicated below:

1st stage (the first compressor and refrigeration circuit) will operate when:

- 1) The thermostat is demanding cooling,
- 2) The vehicle is being powered by either shore line or the on-board generator.

2nd stage (the second compressor and refrigeration circuit) will operate when:

- 1) The thermostat senses room temperature is 2 degrees higher than setpoint,
- 2) The vehicle has enough power.

B. Heat Pump

Heat operation always energizes both refrigeration circuits with a 30 second delay between compressor 1 start-up and compressor 2 start-up, however, only refrigeration circuit #1 operates if power is not available for circuit #2.

Thermostat operation is described in operation instructions packed with the thermostat.

III. MAINTENANCE

One of the biggest advantages of owning an RV Products heat pump is that the maintenance needed to keep the unit in good care is minimal.

In fact, the only maintenance that must be taken care of on a regular basis is the cleaning or replacement of the units return air filters.

The manufacturer of your vehicle determines the number, size and location of the return air filters. Be sure to contact your dealer should you have any questions concerning the number of filters used and their location.

The return air filters of this system will accumulate dust and dirt more quickly than ceiling mounted systems. We recommend that the filters be checked on a weekly basis.

If the filters are not cleaned or replaced at regular intervals, they may become partially clogged with lint and dirt. A clogged filter will produce a loss of air volume and may eventually cause equipment damage.

Do not operate the heat pump without return air filters. Operating the system without filters allows the lint and dirt that is normally stopped by the filter to accumulate on the cooling coil of the heat pump. This also will lead to a loss of air volume, possible equipment damage and an expensive cleaning process.

Periodically (once or twice a season), inspect the outdoor coil and brush off any accumulated residue with a soft bristled brush.

IV. WARRANTY

Let's face it. Sometimes even the best products may need service. To obtain warranty service on your RV Products air conditioner, please contact your selling dealer, or you may access our web site on the Internet at www.rvcomfort.com for answers to the most frequently asked questions and service center locations.

RV Products support help may be accessed by E-mail at RVPSupport@Airxcel.com.

All written correspondence should be directed to:

**RV Products
A Division of Airxcel, Inc.
P.O. Box 4020
Wichita, KS 67204**

IMPORTANT

1. Carefully read your limited two year product warranty which is packed with the product.
2. An optional three year extended parts only contract is available at an additional cost of \$89.95. To obtain this optional three year parts contract, fill out the application card stapled to the front of this envelope. Please mail the card and a check or money order to the address above. Applications must be made **within ninety (90) days** of the original purchase.
3. Inquiries about your RV Products air conditioner must include the model and serial numbers and the date of purchase. The model and serial numbers can be found on the unit rating plate.

**RV Products
A Division of Airxcel, Inc.
P.O. Box 4020
Wichita, KS 67204**