



DATA INQUIRY SHEET

6532-871

PACKAGED HEAT PUMP

Capacity (Actual BTUH)	Cooling - 7,700 Heating - 8,100
Electrical Rating	115 VAC, 60 HZ, 1 Phase
Cooling Full Load AMP's at A.R.I. Standard Condition	Compressor - 6.7 Outdoor Fan Motor - 2.56 Total - 9.26
Running Watts: (Cooling) A.R.I. Standard Condition (80 F. DB/67 F. WB Indoor, 95 F. DB Outdoor)	1100
Running Watts: (Heating) A.R.I. Standard Condition (70 F. Indoor), 47 F. DB/43 F. WB Outdoor @ 115 VAC	1075
Compressor Locked Rotor Amps	45.6
Metering Device	Biflow Restrictor
Refrigerant Charge	18.5 oz.
Evaporator Air Delivery (CFM)	208 CFM
Generator Size	See "Generators" Below
Unit Weight (pounds)	94.5 lbs.
Use time delay fuse or circuit breaker (U.L. H.A.C.R. Type C.S.A.) Rated at 15 amps. Supply wires 12 AWG Min. (Copper)	

GENERATORS:

It is not the policy of RV Products to size generators for application in Recreation Vehicles or related structures. However, when sizing generators, the total electrical power consumption in Watts must be determined and taken into consideration, such as:

- A. Maximum running watts of the air conditioner at A.R.I. maximum operating conditions (See Specifications).
- B. Power consumption of electronic ovens, toasters, coffeemakers, television sets, refrigerators, lights, etc.
- C. Generators do lose capacity under the following conditions: (1) Altitude increases above sea level, (2) Temperature increases above certain outdoor design temperatures and (3) Lack of maintenance.

RV Products
A Division of Airxcel, Inc.
P.O. Box 4020
Wichita, KS 67204

