



DATA INQUIRY SHEET
6636 TWO TON
HIGH EFFICIENCY
PACKAGED AIR CONDITIONER

Specifications By Model Number	System 1 & 2	System 1 Only
Electrical Rating	115 VAC, 60 HZ, 1 Phase	
Cooling Full Load AMP's at A.R.I. Standard Condition	Compressor - System 1 & 2 - 7.6 Fan Motor - Outdoor Fan Hi - 3.3 Fan Motor - Outdoor Blower Hi - 2.4 Total - 20.9	Compressor - System 1 - 7.6 Fan Motor - Outdoor Fan Lo - 2.4 Fan Motor - Outdoor Blower Lo - 1.3 Total - 11.3
Running Watts: (Cooling) A.R.I. Standard Condition (80 F. DB/67 F. WB Indoor, 95 F. DB Outdoor at 103.5 VAC)	2500	1475
Running Watts: (Cooling) A.R.I. Maximum Condition (95 F. DB/71 F. WB Indoor 115 F. DB Outdoor at 103.5 VAC)	3120	1775
Compressor Locked Rotor Amps	48.3	
Electronic Thermostat Set Temperature Range	40 F. to 90 F.	
Metering Device	Capillary Tube	
Refrigerant Charge	21.0 oz. each system	21.0 oz.
Evaporator Air Delivery (CFM)	600 @ .4 External Static	
Installed Weight (pounds)	200	

ACCESSORIES AVAILABLE:

6795B3451 Electronic 12 VDC Wall Mounted Thermostat

6795B4351 35' Thermostat Cable for termination at both the air conditioner and electronic thermostat.

RV Products
A Division of Airxcel, Inc.
P.O. Box 4020
Wichita, KS 67204

